



Alpha Provac Mono 50 CF

TECHNICAL SPECIFICATIONS

Product Description

MONO GRADE Oil SAE 50 formulated from the finest base oils with high-performance additives to provide high-quality protection and lubrication for the internal engine parts of heavy-duty vehicles. It is also designed to provide triple protection to preserve the engine and oil durability, helping to reduce maintenance and increase vehicle reliability.

Compliant with Egyptian specifications and American Petroleum Institute specifications (API CF)

Applications And Benifits :

- Guarantees excellent engine lubrication in the most severe conditions.
- Excellent anti-wear and anti corrosion properties.
- Excellent detergency and dispersancy levels.
- Excellent viscosity stability in operation in the latest Diesel engines especially for turbocharged engines.
- Easier cold startExceptional performances due to the lubricant's synthetic base stocks and high performance additives.

TESTS	TEST METHODS	MONO CF
GRADE		SAE 50 API CF
Appearance	VISUAL	CLEAR
Colour	ASTM D1500	..
Density @ 15°C	ASTM D4053	0.900
Flash point °C	ASTM D 92	> 220
Pour point °C	ASTM D97	-9
KIN.Viscosity @40c	ASTM D7042	200
KIN.Viscosity @100c	ASTM D7042	19.7
Viscosity index	ASTM D2270	>98
CCS@-20	ASTM D664	..
Foam Test	ASTM D892	0/0
TBN	ASTM D2896	10
Water Content	ASTM D6304	NILL

Health, Safety and Environment

This product is unlikely to present any significant health and safety hazards when used in the recommended application. Avoid contact with skin. Wash immediately with soap and water after skin contact. Do not discharge into drains, soil or water.

For further detail regarding storage, safe handling, and disposal of product, please refer to product SDS or contact us at : www.alphaenergy.com.eg